

### SX'2 White with Cover

Weight : 1,8 kg

**HINGES AND FASTENERS**

Delivered with 2 stainless steel screws, 6x70 (x5CrNi 18/10) = AISI 304

PP Hinges

Plastic Hinges  
Ref. : 7SX9001D

Stainless steel hinges  
Ref. : 7SX900104D

### Technical Instructions

**Material** : Duroplast.

**Hinges** : Stainless steel hinges and screws. Adjusting hinges.

**Resistance in moist environment** : 200 hours in a vapour bath heated at 50°C and with 99% of moisture content. Global immersion in water heated at 65°C during 1 hour. \*

**Mechanical Resistance** : 30 000 lift and release cycles as required by NF Norm. Static test : 150 kg. Dynamic test : 75 kg for 30 000 cycles. \*

**Chemical Resistance** : Tested to resist sulfamic acid, uric acid, caustic bleaches and other cleaning products available in stores. \*

**Cleaning** : Cleaning with a sponge and with non abrasive cleaning products for toilet seats. It is advised to lift the seat while cleaning the bowl. It is not recommended to use cleaning products containing chlorine, acids and other corrosive chemicals.

**Warranty** : 2 years

#### RECOMMENDATIONS SX'2 Plastic Hinges \*\*

Residential	+++
Commercial / Institutional	+
Hospitality / Hotels	+
Health Facilities	-

#### RECOMMENDATIONS SX'2 Stainless Steel Hinges \*\*

Residential	+++
Commercial / Institutional	++
Hospitality / Hotels	++
Health Facilities	+

\* according to the requirements of the NF Norm for toilet seats

\*\* according to the mechanical and physical requirements of each environment

Legend :  
**from +++** : perfectly suitable  
**to ---** : completely unsuitable